

3M Scotchlite™
Reflective Material

SAFETY

BRONCO 3.0

| 4996





MADE FOR
NEW ZEALAND
SINCE 1934

SAFETY

BRONCO 3.0

UPPER: NUBUCK BULLHIDE LEATHER | **4996**
COLOUR: WHEAT

HEAVY INDUSTRIAL ENVIRONMENTS

ZIP SIDE

WIDE FITTING

HEIGHT | 135mm

SIZE: 4-14



CUSHION
CORE 3.0



STEEL
TOE CAP



STEEL
TOE CAP



PENETRATION
RESISTANT



WATER
RESISTANT
LEATHER



300°C
RESISTANT



SLIP
RESISTANT



OIL/ACID
RESISTANT



ORGANIC
FAT/OIL
RESISTANT



ELECTRICAL
HAZARD
RESISTANT



COOLMAX
LINING



CUSHION
CORE 3.0

The Bronco 3.0 combines our toughest safety features with our best cushioning technology in one sleek wheat package.

- Revolutionary world-first CushionCore 3.0 comfort technology combines two compounds of PU injected into the midsole providing superior shock absorption at the heel while also providing rebound at the forefront as you step
- Nitrile Rubber outsole with aggressive self-clearing tread pattern providing superior grip, stability and abrasion resistance. Rubber outsole increases cut and slip resistance and is resistant to hydrolysis and microbial attack
- Super cushioning Comf2Bull Quad-Max footbed made of a soft PU with a cushioning heel that's also antibacterial and washable
- Wheat Nubuck water-resistant Bullhide leather
- Coolmax® lining fabric helps transport moisture away from your foot, through the fabric, where it can evaporate quickly
- Broad fitting 200 joule impact resistant Type 1 steel toe cap
- Non-metallic penetration-resistant insole which resists penetration even by small diameter nails and other objects
- Tough Coil Zip and zip gusset to help stop water, dust and mud entering the boot
- Heavy duty TPU toe guard for extra scuff protection
- Scratchguard heel for added durability and extra reinforcement

PU - Polyurethane | TPU - Thermoplastic Polyurethane
EVA - Ethel Vinyl Acetate | PUR - Polyurethane Rubber



Refer to our website for further details of the 30 day comfort guarantee and the manufacturer's 6 month warranty.

CERTIFIED TO:
STANDARD AS
2210.3:2019

CLASSIFICATION
1 - ID2815

ASTM F2413 - 18
INCLUDING EH
[CLAUSE 5.6]

PRODUCT CERTIFICATION



BSI Certified Product